



755-201

08/596712

A

1 APPARATUS AND METHOD FOR DRAINING,  
2 CLEANING, AND FILLING AN AQUARIUM

3 **BACKGROUND OF THE INVENTION**

4 Field of the Invention

5 This invention pertains to the field of pets and pet supplies.  
6 More particularly, the invention pertains to a compact device for  
7 draining, cleaning, and filling an aquarium, especially one that has  
8 gravel on the bottom, and that performs such services with the least  
9 disturbance to the flora and fauna living therein.

10 Description of the Prior Art

11 What child has not watched, in absolute fascination, the  
12 movement of brightly colored fish swimming about in an aquarium?  
13 The fascination of fish in an aquarium has spread to the point that  
14 they are seen gracing business offices and restaurants. Fresh water  
15 fish and salt water fish display distinctive colors under a variety  
16 of lights and it is rare that such displays do not entertain  
17 onlookers.

18 As in most instances, however, a lot of work goes into the  
19 beautification of the aquariums. Fish are like humans in that they  
20 survive by eating food, and their normal digestive activity requires  
21 that they periodically void their bodies of the waste materials.  
22 In an effort to remove this waste, filters are submerged in aquariums  
23 through which water passes. In many cases, an underwater filter is  
24 placed on the bottom of the aquarium tank over which a layer of  
25 gravel particles is arranged. The waste material falls to the bottom  
26 of the tank onto the gravel, and the general flow of water is  
27 directed downward, through the gravel, to bring fresh water into  
28 contact with the waste so that some of it is digested by natural

1 processes.

2        Depending upon the size of the aquarium and the type and number  
3 of inhabitants maintained therein, it is often necessary to physical-  
4 ly remove the sediment and impurities from the gravel and, at the  
5 same time, clean the interior walls and glass of the thin film of  
6 plant life that grows thereover which gradually renders the glass  
7 opaque. As a general rule, in cleaning aquariums, not more than  
8 about one-third of the water should be removed to prevent the shock  
9 of the new, make-up water from adversely affecting the inhabitants.

10        A number of processes and apparatuses have been developed for  
11 performing the draining, cleaning and refilling work. United States  
12 patents 1,826,829; 1,930,284; 1,950,172; 2,112,290; 2,741,997;  
13 2,956,507; 3,304,564; 3,734,853; 3,738,620; 3,741,158; and, 4,610,784  
14 have been issued in an effort to make this cleaning process easier  
15 for the serious aquarium aficionado. The closest prior art appears  
16 to be the Reyniers patent (4,610,784) and the Green, et al patent  
17 (3,304,564).

18        In Reyniers, a flexible hose is provided having opposite ends,  
19 where one end is connected to one end of a larger diameter tube.  
20 The other end of the tube is placed adjacent the gravel covering the  
21 floor of the aquarium. Means are provided, specifically a valve and  
22 a fitting, for connection to the end of a faucet that contains a  
23 venturi section. When the faucet is turned on, one position of the  
24 valve causes the water running out of the faucet to draw water in  
25 through the hose from the aquarium for discharge into the drain below  
26 the faucet. This water flow causes gravel to be picked up and swept  
27 into the gravel tube where, supposedly, the gravel particles "churn"  
28 and rid themselves of sediment and fish droppings that are swept into

1 the hose and ultimately discharged in the drain while the gravel  
2 drops back to the bottom of the aquarium.

A 3 This product has some serious disadvantages that <sup>has</sup> ~~have~~ prevented  
4 its wide spread acceptance. It takes a rather significant flow of  
5 water to draw the gravel up into the gravel tube. Usually, by the  
6 time the user has established the appropriate flow, much of the water  
7 volume in the aquarium tank has been drained and the process must  
8 be stopped so that the one-third volume change rule is not violated.  
9 In addition, when the proper flow has been achieved, the gravel  
10 particles do not grind together with sufficient force to rid them  
11 of all the sediment and impurities, so the cleaning cycle is not  
12 fully completed. After some of the gravel particles do churn in the  
13 gravel tube, there is nothing to cause them to fall back to the floor  
14 of the aquarium except if the upward flow in the gravel tube is  
15 interrupted. The continual starting and stopping of the flow in the  
16 tube causes sediment and impurities to be stirred up at the bottom  
17 of the tank and this disturbs the inhabitants. Finally, the bottom  
18 of the gravel tube is flat. In order to cause sufficient velocity  
19 of water upward in the gravel tube, the flat end of the tube must  
20 be placed almost fully against the gravel. When this occurs, some  
21 gravel is swept up into the gravel tube. The slightest lifting of  
22 the tube from the floor of the tank will allow more water to enter  
23 the tube and lower the upward velocity. This allows the gravel to  
24 fall out of the tube without churning to rid itself of sediment and  
25 impurities. For best results in using this apparatus, one must have  
26 a very steady hand as well as be able to manipulate valves, hoses,  
27 and the gravel tube swiftly and with great care. These traits are  
28 not always present in those who care for aquariums.

- 1
- 2
- 3
- 4
- 5
- 6
- 7
- 8
- 9
- 0
- 1
- 2
- 3
- 4
- 5
- 6
- 7
- 8
- 9
- 0
- 1
- 2
- 3
- 4
- 5
- 6
- 7
- 8

A frame-supported, tooth-shaped grille is provided that has formed therein a plurality of openings to allow passage of water, sediment and impurities from the tank into the discharge hose but not the gravel. The operator manipulates the tube to cause the grille to push the gravel about the floor of the tank so that gravel particles physically bump against each other and their surfaces grind together to break off the sediment and impurities. The continual flow of water into the grille, through that part of the grille not in contact with the gravel particles, allows the separated sediment and impurities to be swept through the grille, up the tube and out the hose. It is no longer necessary to refer to the tube as the "gravel" tube because the grille prevents any entrance whatsoever of gravel into the tube or the hose. All intercontact between gravel particles takes place outside the tube and the tube is merely used as a handle to manipulate the grille about the floor of the aquarium tank.

The grille is singular in design and contains screens that are arranged at angles to each other. This design presents one screen or portion thereof in contact with, or exposed to, the aquarium water

1 while one or more other screens are being used to plow the gravel  
2 particles along the floor of the aquarium. This is totally different  
3 from the flat-ended gravel tube of the Reyniers patent and the Green,  
4 et al patent, and clearly provides a more constant flow of aquarium  
5 water upward through the tube while the operator is physically  
6 causing the particles to bump and grind together by the power of  
7 his/her hand.

8 In addition, this invention comes in three embodiments; the  
9 first embodiment is made up of a length of flexible hose having first  
10 and second opposite ends, a tube including an upper end for connec-  
11 tion to the first opposite end of the flexible hose, and a grille  
12 comprising screens arranged at angles to each other for attachment  
13 to the lower end of the tube for contact with the gravel along the  
14 bottom of the aquarium tank. A first means is provided for connect-  
15 ing the second end of the elongated flexible hose to a water source,  
16 such as a faucet, including a venturi section for causing a vacuum  
17 in the flexible hose to start the draining process. This embodiment  
18 may also include a second means for causing selective and alternative  
19 flow of water from the aquarium tank through the tube and the  
20 flexible hose to a drain and a flow of water from the water source  
21 through the elongated flexible hose to the aquarium tank for  
22 refilling the aquarium tank.

23 The second embodiment does not use the first or second means,  
24 but provides the cleaning action when the other or second end of the  
25 flexible hose is placed lower than the first end and a natural siphon  
26 action started, such as by creating a partial vacuum in the flexible  
27 hose. The water, with entrained sediment and impurities, is removed  
28 from the tank by this siphon action.

1       The third embodiment of the invention is the inclusion of a  
2 water pump, in place of the natural siphon, and connection of the  
3 pump inlet to the second end of the flexible hose such that, when  
4 the pump is turned on, water, sediment and impurities are pumped  
5 through the grille, tube, and hose to be discharged by the pump  
6 outlet in a drain or other place.

7       All of these embodiments utilize the novel grille at the bottom  
8 end of the tube to physically cause separation of the sediment and  
9 impurities from the gravel outside the tube.

10       The invention comprises an elongated flexible hose having  
11 opposite terminal ends, a tube including an upper end for connection  
12 to one of the opposite ends of said flexible hose, and a lower end  
13 for connection to a grille to be immersed in the aquarium tank so  
14 that the grille may be placed adjacent the bottom of the aquarium  
15 tank for contact with the gravel to move the gravel about such that,  
16 when a vacuum or water-drawing action is maintained in the tube and  
17 hose to remove water from the aquarium, the gravel particles are  
18 forced by movement of the grille to bump and rub against each other  
19 to dislodge the sediment and impurities (fish droppings) therefrom.  
20 The sediment and droppings thereafter are swept by the water flow  
21 through the openings in the grille up the tube and through the hose  
22 to a drain without the entrance of gravel into the tube or hose.  
23 Part of the grille is always exposed to the water in the aquarium  
24 tank to facilitate the flow of water up the tube.

25       The main difference between the embodiments is the manner in  
26 which the water is caused to drain out of the aquarium tank through  
27 the flexible hose. In the first embodiment, the water-drawing action  
28 is caused and maintained by suction generated in the venturi section

1 of a fitting attached to a water faucet. This embodiment may also  
2 include a means for refilling the aquarium. In the second embodi-  
3 ment, it is caused and maintained by natural siphoning action. And  
4 in the third embodiment, it is caused and maintained by a mechanical  
5 pump.

6 Accordingly, the main object of this invention is a highly  
7 functional device for draining, cleaning and refilling an aquarium  
8 tank and, in cleaning the tank, to cause the gravel particles  
9 covering the floor thereof to be pushed about to bump and grind  
10 together to dislodge sediment and impurities, including fish  
11 droppings, from the particles while providing an uninterrupted flow  
12 of water along the bottom of the tank and up into the tube and hose  
13 for discarding the sediment and impurities. Other objects of the  
14 invention include an apparatus for separating the sediment and  
15 impurities from the underlying gravel floor and sweeping them from  
16 the floor and other places of higher concentration to clean the  
17 aquarium tank with efficiency and dispatch; an apparatus for  
18 cleaning, draining and refilling the aquarium tank where the gravel  
19 remains on the floor of the tank and is prevented from entering the  
20 tube or any portion of the apparatus; an apparatus that allows the  
21 operator to move the gravel about, to cause separation of sediment  
22 and impurities therefrom, and removal of the sediment and impurities  
23 without the need to constantly adjust the flow of water into the  
24 tube; an apparatus for cleaning an aquarium tank where the agitation  
25 of the gravel particles is maintained along the floor of the tank  
26 in the presence of a continuous flow of water up the tube and out  
27 the hose to draw out all sediment and impurities that are stirred  
28 up by the cleaning action; an apparatus that allows faster cleaning

1 of aquarium tanks than apparatuses in the prior art so that water  
2 is saved in the aquarium tank and the requirement for new water in  
3 the tank is curtailed such that the burden on the environment is  
4 substantially lessened; and, an apparatus that may be used by persons  
5 of lesser skill than those using the prior art devices so that  
6 additional training is not required.

7 These and other objects of the invention may be determined by  
8 reading the following Description of the Preferred Embodiments taken  
9 together with the drawings appended hereto. The scope of protection  
10 sought by the inventor may be gleaned from a fair reading of the  
11 claims that conclude this specification.

12 Description of the Drawings

13 Figure 1 is a perspective view of one embodiment of the  
14 apparatus of this invention shown in use with a typical faucet pump  
15 with an aquarium tank;

16 Figure 2 is a perspective view of another embodiment of the  
17 apparatus of this invention shown in use in a siphon mode with an  
18 aquarium tank;

19 Figure 3 is a partial perspective view of another embodiment  
20 of the apparatus of this invention shown in use with a typical water  
21 displacement pump to pump water, sediment and impurities out of an  
22 aquarium tank;

23 Figure 4 is an enlarged cross-sectional elevation view of the  
24 tube interposed between the flexible hose and the grille for use in  
25 the embodiments shown in Figures 1, 2 and 3;

26 Figure 5 is an enlarged cross-section view of a typical flow  
27 control valve that may be used in the apparatus shown in the  
28 embodiments shown in Figures 1, 2 and 3;



1 Figure 6 is an enlarged cross-section elevational view of a  
2 faucet pump embodied in the apparatus illustrated in Figure 1 and  
3 with the faucet pump flow control arrangement positioned such that  
4 water will flow to the drain;

5 Figure 7 is a view similar to Figure 6 and showing the faucet  
6 pump-flow control arrangement positioned such that water will flow  
7 from the faucet into the aquarium tank;

8 Figure 8 is a cross-section view taken along lines 8-8 in Figure  
9 6.

10 Figure 9 is a perspective view of the preferred embodiment of  
11 the grille of this invention;

12 Figure 10 is a side elevational view of the embodiment shown  
13 in Figure 9;

14 Figure 11 is a front elevational view of the embodiment shown  
15 in Figure 9;

16 Figure 12 is a top view of the embodiment shown in Figure 9;  
17 and,

18 Figures 13a, 13b, and 13c are illustrative drawings showing how  
19 the grille of this invention insures a continuous flow of water up  
20 through the tube no matter in what position the grille is embedded  
21 in the gravel at the bottom of the aquarium tank.

#### 22 DESCRIPTION OF THE PREFERRED EMBODIMENTS

23 Turning now to the drawings, where like elements are identified  
24 by like numbers throughout the 15 figures, Figures 1 and 2 show a  
25 typical aquarium tank 1 comprising <sup>spaced-apart</sup> ~~spaced-part~~ glass or clear plastic  
26 sides 3 extending vertically upward from a flat bottom (not shown)  
27 and held together in a watertight configuration along their respec-  
28 tive side edges 5 by a metal frame 7. Aquarium 1 has an open top

1 9 and a floor 13 covered with a layer of gravel 15 and filled with  
2 water 17 and including flora and fauna (not labelled).

3 In many cases, there is a flat plate set under the gravel that  
4 supports what is known as an "under-gravel" filter. Fish droppings  
5 and other debris naturally fall or sink to the gravel and become  
6 intermeshed therewith. If not periodically removed from the gravel,  
7 the droppings and other debris will sour the entire environment and  
8 place a stress on the inhabitants therein. In addition, there will  
9 be a significant amount of toxic solubilized materials formed in the  
10 water layer adjacent the gravel and this must be removed to retain  
11 comfort in the water.

12 As shown in Figures 1 and 2, an elongated flexible hose 19 is  
13 provided having first and second opposite ends 21 and 25, respective-  
14 ly. A tube 27 is also provided that includes an upper distal end  
15 29 for connection to first end 21 of flexible hose 19. The other  
16 or lower distal end 31 of tube 27 is to be attached to a grille 33  
17 and said grille and tube end 31 are immersed in water 17. Grille  
18 33 will be described in detail later in this specification.

19 In the embodiment shown in Figure 1, flexible hose 19 is  
20 interconnected, intermediate its ends 21 and 25, to an optional flow  
21 control valve 37 to control the flow of water passing through hose  
22 19. As shown in Figure 5, flow control valve 37 comprises a valve  
23 body 39, including hose receptacles 40a and 40b having formed  
24 thereacross a flow bore 41 for flow of water between hose connections  
25 40a and 40b set on opposite sides of body 39. A valve bore 42 is  
26 formed cross-ways in body 39 into which is pivotally positioned a  
27 valve stem 43 having a turnable handle 44 at one end and a cross-bore  
28 45 formed transversely thereacross to align with said flow bore 41

1 in various positions to allow a flow of water thereacross as  
2 determined by the position of handle 44.

3 As shown in Figure 1, in the first embodiment of this invention,  
4 flexible hose second end 25 is attached to a first means 46 for  
5 connection to a flowing water source, such as a faucet 47, that can  
6 draw water through hose 19. Means 46 is shown in greater detail in  
7 Figure 6 and shows it to comprise a base 49, containing a main faucet  
8 water transfer tube 51, with a surrounding cap 53 for attaching the  
9 top end 55 of said tube in axial, watertight alignment with the  
10 outlet of faucet 47 for directing a flow of faucet water downward,  
11 through said tube and out the bottom end 57 thereof toward a drain  
12 59 located in a sink 61. Tube 51 includes a narrower diameter  
13 section 63, intermediate tube ends 55 and 57, for decreasing the  
14 diameter of the stream of water passing downward therethrough. A  
15 side tube 65 is formed in base 49 and contains a surrounding cap 67  
16 for connection to flexible hose second end 25. The introduction of  
17 side tube 65 is transverse to the axis of main faucet water transfer  
18 tube 51 and near the area of the narrower flow to take advantage of  
19 the venturi effect caused by this narrower area of flow. Base 49 also  
20 includes a bottom tube section 69 of wider diameter than the venturi  
21 section for carrying both faucet water and, when desired, aquarium  
22 tank water with its entrained sediment and impurities, downward  
23 through bottom tube end 57 into drain 59.

24 This first embodiment may be joined with a second means 71 for  
25 causing selective and alternative flow of water from aquarium tank  
26 1 through tube 27 and elongated flexible hose 19 to drain 59 and,  
27 in addition, a flow of water from faucet 47 through hose 19 and tube  
28 27 for refilling aquarium tank 1. This second means 71 is shown in

greater detail in Figures 6, 7 and 8 and shows a valve 73 mounted to tube bottom end 57. Valve 73 includes a shut-off plate 75 transversely mounted by two screws 77 for manual, reciprocal motion from a first position, shown in Figure 6, spaced-apart from tube end 57 (allowing water to flow through tube bottom end 57) to a second position, shown in Figure 7, abutted against tube end 57 (diverting water upward from tube bottom end 57 to flow out side tube 65).

As shown in Figure 2, in the second embodiment of this invention, the second end 25 of flexible hose 19 is placed below the level of tank gravel 15, such as into sink 61 containing drain 59. In this configuration, a natural siphoning action may be started, by simply causing a partial vacuum in hose 19, whereby the difference in atmospheric pressure on the surface of water 17 and at flexible hose second end 25 will support a flow of aquarium water out of tank 1 and into sink 61. In this configuration, water may be obtained for filling aquarium tank 1 by attaching flexible hose end 25 directly to water faucet 47 after the draining operation is completed.

As shown in Figure 3, in the third embodiment of this invention, flexible hose second end 25 is connected to the inlet 79 of a typical water pump 81 of the type that can pump water out of aquarium tank 1, such as by suction, displacement, turbine action and the like. As shown in Figure 3, pump 81 is a common displacement type electrical pump containing a vibration unit inside which causes suction at top inlet 79 and pumps water (with sediment and impurities) from tank 1 out through the pump bottom outlet 83. Pump 81 obtains electrical power through electrical line 85 to pump water from tank 1 to drain 59 in sink 61.

Tube 27 is shown in detail in Figure 4 and shows upper distal

1 end 29 closed over by a tight fitting cap 91 that has a bore 93  
2 formed therethrough and a surrounding flared stub 95 adaptable for  
3 attaching tube upper distal end 29 to flexible hose first end 21.  
4 Tube 27 may take on a variety of configurations. It is not necessary  
5 that it be larger in diameter than flexible hose 19; in fact, it may  
6 be the same or smaller in diameter. It may also be made in separate  
7 pieces or lengths that may be connected end-to-end to provide a tube  
8 of adjustable length for use in small, as well as large (and deep),  
9 aquariums as is already known in the prior art. It may be opaque  
10 or transparent and it may be made of metal or plastic. And, it may  
11 be coupled to a handle; however, for the most part, one can use the  
12 upper part of tube 27 as its own handle.

13 As shown in Figures 9-12, grille 33 is formed with a plurality  
14 of small apertures 96 that are narrower than the width of the gravel  
15 particles at the bottom of the aquarium tank. When grille 33 is  
16 moved into contact with the gravel, apertures 96 are of a size to  
17 allow passage of water, sediment and impurities therethrough but are  
18 not so large as to allow passage of gravel particles therethrough.  
19 As further shown, grille 33 of this invention comprises a planar base  
20 frame 97 defined by sides, such as rectangular sides 101 that form  
21 a perimeter 103 thereabout. An opening 105 is formed in frame 97,  
22 preferably centrally therein, about which, on one side of frame 97,  
23 is located a collar 107 for attachment to tube lower distal end 31.  
24 It is preferred that collar 107 be attached about the entire opening  
25 in tube lower distal end 31. The attachment may be permanent, such  
26 as by using a thin film of adhesive between collar 107 and tube end  
27 31 or may be removeably attached such as by making collar 107  
28 frictionally tight fitting about tube end 31.

1 A plurality of support arms 109 extends from base frame 97 on  
2 the opposite side of said frame from the connection to tube 27, said  
3 arms 109 extending in convergent manner to form a plurality of tooth-  
4 shaped lattices 113. As shown in Figures 9-12, lattices 113 are  
5 formed in teeth-shape and are arranged parallel to each other. One  
6 or more screens 115, having said apertures 96 formed therethrough,  
7 are formed over lattices 113 to create the gravel contact surface  
8 of grille 33. Each tooth-shaped screen 115 is further defined by  
9 a bottom support 117 and a top perimeter 119 attached to frame 97.  
10 The distance between bottom supports 117 and their respective top  
11 perimeters 119 of each tooth-shaped screen is labeled "L".

12 As further shown in Figures 9-12, the preferred embodiment of  
13 this invention is shown where screen 115, lattices 113, and support  
14 arms 109 are made in one monolithic unit such as by injection  
15 molding. In addition, while apertures 96 may be in the form of mere  
16 holes, the preferred embodiment of said apertures is a plurality of  
17 slots 96, arranged in side-by-side position, formed in screens 115,  
18 that extend from near bottom support 117 to near top perimeter 119  
19 and of a width sufficient to pass sediment and impurities from  
20 outside grille 33 to inside the interior chamber 125, formed by  
21 screens 115 and base frame 97 that defines grille 33. Other forms  
22 of apertures are fully contemplated in this invention such as holes,  
23 round or otherwise.

24 As shown in Figures 13a-13c, it is preferred that tooth-shaped  
25 screens 115 are formed in a plurality wherein they are spaced from  
26 each other a distance such that a portion of one said screen is  
27 always exposed to water in the tank regardless of the position of  
28 said other screen. Two such tooth-shaped screens 115 would fill this

1 requirement, however, for molding, internal strength, and other  
2 considerations, the plurality shown in Figures 13a-13c are considered  
3 preferred.

4 The length "L" of tooth-shaped screens 115 is set noticeably  
5 longer than the depth of gravel normally encountered on the floor  
6 of aquarium tanks. This is to allow a continuous flow of tank water  
7 into interior chamber 125 while grille 33 is in contact with the  
8 gravel to aid in sweeping the sediment and impurities in through said  
9 apertures 96 into chamber 125, up tube 27 and through hose 19 to the  
10 drain. This unique aspect of the invention is shown in Figures 13a,  
11 13b, and 13c, namely that no matter how tube 27 is tilted or angled,  
12 grille 33 still maintains part of screens 115 above and out of  
13 contact with the gravel to allow a constant flow of water there-  
14 through and upward through tube 27 and hose 19 to the drain.

15 This action of causing the gravel particles to bump and rub  
16 together outside the tube is totally different from Reyniers' patent  
17 where the flow of water into the lower end of the gravel tube must  
18 be maintained at a critical value i.e., sufficient to cause gravel  
19 to be drawn into the gravel tube, and not strong enough to have the  
20 gravel pass further upward into flexible hose 19. Such criticality  
21 in Reyniers has led to poor acceptance of this practice. In the  
22 instant invention, all the bumping and grinding ("churning") of the  
23 gravel takes place outside the tube.

24 When using the embodiment shown in Figure 1, with first and  
25 second means 46 and 71, base 49 is fastened to faucet 47 and flexible  
26 hose second end 25 attached to side tube 65 and the faucet turned  
27 on to create a vacuum in flexible hose 19. Flow control valve 37  
28 is adjusted to the desires of the operator and then the operator

1 presses slightly downward on tube 27 to force grille 33 into contact  
2 with the gravel on the bottom of tank 1. The operator moves grille  
3 33 about, alternately plowing up and smoothing down gravel while  
4 causing the gravel particles to bump against each other and their  
5 respective outer surfaces to grind together to dislodge the sediment  
6 and the impurities that have gathered along the bottom of tank 1 in  
7 the gravel. The flow of water into chamber 125, grille 33, tube 27  
8 and out hose 19 into drain 59 will carry sediment and impurities with  
9 it.

10 When using the embodiment shown in Figure 2, flexible hose  
11 second end 25 is placed lower than first end 21 and a small amount  
12 of suction is started in flexible hose 19, such as by using a  
13 "squeeze ball" type pump or by sucking on hose end 25. A natural  
14 siphon action is thereby started and the aquarium water, with  
15 entrained sediment and impurities, is removed from the tank through  
16 chamber 125, grille 33, tube 27, and flexible hose 19 by this siphon  
17 action.

18 When using the embodiment shown in Figure 3, flexible hose  
19 second end 25 is attached to inlet 79 of water displacement pump 81  
20 and electrical power delivered through electrical line 85 to start  
21 the pump action and draw water in through chamber 125, grille 33,  
22 up tube 27, through flexible hose 19, through pump 81 and out pump  
23 outlet 83 to drain 59.

24 After the operator has removed about one-third of the water from  
25 tank 1, (s)he either turns off flow control valve 37 and works in  
26 the partially emptied aquarium tank, or, in the case of the invention  
27 shown in Figure 1, closes shut-off valve 73 so that shut-off plate  
28 75 is moved to its second position, against tube bottom end 57, to



1 force the flow of faucet (fresh) water into side tube 65, hose 19,  
2 tube 27 and out grille 33 to refill aquarium tank 1.

3 While the invention has been described with reference to a  
4 particular embodiment thereof, those skilled in the art will be able  
5 to make various modifications to the described embodiment of the  
6 invention without departing from the true spirit and scope thereof.  
7 It is intended that all combinations of elements and steps which  
8 perform substantially the same function in substantially the same  
9 way to achieve substantially the same results are within the scope  
10 of this invention.